



(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
23.02.2000 Bulletin 2000/08

(51) Int Cl.7: **F16D 27/115, F16H 48/12,**
F16H 48/20, B60K 23/04
// F16H48:30

(43) Date of publication A2:
04.11.1998 Bulletin 1998/45

(21) Application number: **98302727.7**

(22) Date of filing: **07.04.1998**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• Joslin, Mark T
Shinagawa-Ku, Tokyo (JP)
• Showalter, Dan J.
Plymouth, Michigan 48170 (US)
• Knowles, Dean P.
Clinton Township, MI 48038 (US)

(30) Priority: **30.04.1997 US 847140**

(71) Applicant: **BORG-WARNER AUTOMOTIVE, INC.**
Sterling Heights, Michigan 48311-8022 (US)

(74) Representative: **Lerwill, John et al**
A.A. Thornton & Co.
235 High Holborn
London, WC1V 7LE (GB)

(54) **Clutch assembly having reaction force circuit**

(57) A clutch assembly for disposition in a motor vehicle drive line includes an internal reaction force circuit. The clutch assembly includes a multiple disc friction clutch (120B) disposed adjacent an operator assembly (168,212) which selectively applies force to the friction clutch to selectively transfer torque therethrough. The clutch components are disposed between fixed stops (132,234) on an elongate member (130b) which func-

tions as a reaction force member to self-contain the reaction force from the clutch operator. The clutch finds application in motor vehicle drive line components such as a rear (secondary) axle in which it is disposed in pairs to independently control torque supplied to each axle and in applications where it is advantageous to contain or ground the reaction force generated by and associated with the clutch operator compactly within the clutch structure rather than its housing.




FIG. 3




FIG. 3